

Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 1 of 14

化学品安全技术说明书

Material Safety Data Sheet (MSDS)

申请商名称 Applicant's name	厦门拓宝科技有限公司 TBB POWER CO., LTD.
申请商地址 Applicant's address	厦门市海沧区东孚镇诗山北路 15 号 NO.15, Shishan North Road, Dongfu of Haicang District 361027, Xiamen City, Fujian Province.P.R.China
产品名称 Name of product	锂电池模组 Lithium Battery Module
型号/规格 Model/type reference	M12-400
标称电压 Nominal Voltage	12.8V (
额定容量/ 能量 Rated Capacity / Energy	400Ah(5120Wh)
版本号 Version number	V1.0 40 40 40 40 40 40 40 40
收样日期: Sample Received Date:	2023.12.25
完成日期: Completed Date:	2024.01.16

Prepared by: Chenqiu bo

Chengin bo

Checked by: Curly Htt

Curly Hu

pproved by: Starry Li

Starry li

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋





Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 2 of 14

第一部分 化学品及企业标识

Section 1- Chemical Product and Company Identification

产品名称	锂电池模组							
Name of product	Lithium Battery Module							
型号/规格 Model/type reference	M12-400							
制造商名称 Manufacturer's name	厦门拓宝科技有限公司 TBB POWER CO., LTD.							
制造商地址 Manufacturer's address	厦门市海沧区东孚镇诗山北路 15 号 NO.15, Shishan North Road, Dongfu of Haicang District 361027, Xiamen City, Fujian Province.P.R.China							
应急电话 Emergency Telephone	邮箱 E-mail							
参考文件 Referenced documents	依据 GB/T 16483-2008 和 ISO 11014: 2009 编写 According to GB/T 16483-2008 & ISO 11014: 2009							

该 MSDS 报告由精准通检测认证(广东)有限公司编写。项目号: PTC24010313201S-LD01.

This MSDS was prepared by Precise Testing & Certification (Guangdong) Co., Ltd. Item Number: PTC24010313201S-LD01.

第二部分 危险性概述

Section 2 - Hazards Identification

危险性类别 Preparation hazards and classification	在正常使用中没有危险,不能拆除,打开,切碎锂电池模组暴露出内部有害成分或燃烧锂电池模组。 Not dangerous with normal use. Do not dismantle, open or shred the Lithium Battery Module ingredients contained within or their ingredients products could be harmful.
外观颜色和气味 Apperance, Color, and Odor	无气无味的固体 Solid object with no odor, no color.
侵入途径 Primary	这些化学物品包含在密封的外壳内。如果内部电芯机械性,热的或电力性的滥用会产生接触性伤害。如果这时出现,暴露的电解液可能导致吸入摄取,眼睛接触和皮

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋



Route(s) of	肤接触的伤害
Exposure	These chemicals are contained in a sealed enclosure. Risk of exposure occurs
	only if the internal cell is mechanically, thermally or electrically abused to the
	point of compromising the enclosure. If this occurs, exposure to the electrolyte
	solution contained within can occur by Inhalation, Ingestion, Eye contact and Skin
	contact
	急性中毒: 看第八部分暴露控制。一旦锂电池模组破裂,内部电芯内的电解质溶液
	将具有腐蚀性,并可能导致烧伤。
	ACUTE (short term): see Section 8 for exposure controls. In the event that this
	internal cell has been ruptured, the electrolyte solution contained within the
	Lithium Battery Module would be corrosive and can cause burns.
	吸入:密封的锂电池模组内不认为有浸入危害。
	Inhalation: Inhalation of materials from a sealed Lithium Battery Module is not an
	expected route of exposure.
	食入:密封的锂电池模组不会被吞咽暴露材料。
	Ingestion: A sealed Lithium Battery Module not be swallowed to expose the
健康危害	material.
Potential Health	皮肤:皮肤接触密封的锂电池模组将不会导致任何伤害。皮肤接触未密封的内部电
Effects:	芯将导致严重的过敏或刺激。
	Skin: Contact between the Lithium Battery Module and skin will not cause any
	harm. Skin contact with contents of an open internal cell can cause severe
	irritation or burns to the skin.
	眼睛:眼睛接触密封的锂电池模组将不会导致任何伤害。眼睛接触未密封的内部电
	芯将导致严重的过敏或刺激。
	Eye: Contact between the Lithium Battery Module and the eye will not cause any
	harm. Eye contact with contents of an open internal cell can cause severe
	irritation or burns to the eye.
	慢性中毒:看第十一部分附加的毒理学资料。
	CHRONIC (long term): see Section 11 for additional toxicological data
致癌物质	不适用
Reported as	Not applicable
carcinogen	

第三部分 成份/组成信息

Section 3 - Composition/Information on Ingredients

本报告是本公司遵循 www.ptc-testing.com服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路 6 号 1 栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 4 of 14

锂电池模组的分类 🗌 物质 🖂 混合物

Classification of the Lithium Battery Module ☐ substance ☐ mixture

化学名称 Chemical Name	CAS 号 CAS Number	百分含量 Weight-%
磷酸铁锂 Lithium iron phosphate	15365-14-7	35.44
石墨 Graphite	7782-42-5	18.48
六氟磷酸锂 lithium hexafluorophosphate	21324-40-3	2.55
铝箔 Aluminum foil	7429-90-5	6,0,00,00
铜 Copper	7440-50-8	13 0 00 00
聚丙烯 Polypropylene	9003-07-0	5 50 50 50 50

注: CAS 号是化学文摘社的注册号。

Note: CAS number is Chemical Abstract Service Registry Number.

N/A: 不适用Not applicable.

第四部分 急救措施

Section 4 - First-aid Measures

吸入	如果吸入未密封的内部电芯,立即转移到有新鲜空气的地方,同时对受污染区域通风。
Inhalation	就医处理。
	If contents of an opened internal cell are inhaled, remove source of contamination
o yo yo	or move victim to fresh air. Obtain medical advice.
皮肤接触	如果皮肤可能接触未密封的内部电芯,尽可能迅速的移开被污染的衣服,鞋和皮革物。
Skin contact	用大量的清水冲洗至少30分钟。速就医。再使用和丢弃衣服,鞋和皮革物之前要充
	分的净化。
	If skin contact with contents of an open internal cell occurs, as quickly as possible
	remove contaminated clothing, shoes and leather goods. Immediately flush with
	lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists,
0 80 80	seek medical attention. Completely decontaminate clothing, shoes and leather

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证 (广东) 有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 5 of 14

6 6 6 T	goods before reuse or discard.
眼睛接触 Eye contact	如果眼睛可能接触未密封的内部电芯,立即用清水冲洗至少 30 分钟保持眼睛睁开,中性盐溶液尽快适用,速就医。
Eye Contact	If eye contact with contents of an open internal cell occurs, immediately flush the
	contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. Take care not to rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to an emergency care facility.
食入 Ingestion	如果食入未密封的内部电芯,不要催吐,立即用清水漱口,速就医。 If ingestion of contents of an open internal cell occurs, DO NOT INDUCE VOMITING. Have victim rinse mouth with water again. Quickly transport victim to
	an emergency care facility.

第五部分 消防措施 Section 5 – Fire-fighting Measures

易燃的特性	如果这个锂电池模组已经破裂,内部电芯中的电解质溶液将是易燃的。像任何密封容						
Flammable	器一样,锂电池模组在暴露于过热时可能会破裂;这可能会导致易燃或腐蚀性物质的						
Properties	释放。						
4 4	In the event that this Lithium Battery Module has been ruptured, the electrolyte						
0 20 20	solution contain within the Internal cell would be flammable. Like any sealed						
. 6. 6.	container, Lithium Battery Module may rupture when exposed to excessive heat;						
0 00 00	this could result in the release of flammable or corrosive materials.						

燃爆危害: 过度加热会导致内含物溢出。

Flammability hazard: Excessive heat can cause inclusions to escape.

燃烧产物和内部物质与空气和水接触的生成物包括: CO, CO_2 , HF, 氟氧化磷, 锂的金属氧化物, 其他刺激性和毒性气体等。

Combustion products and internal substances in contact with air and water products include: CO, CO₂, HF, phosphorus fluoride oxide, metal oxides of lithium, other irritant and toxic gases.

使用合适燃烧材料的灭火器,如:干粉,二氧化碳,砂子,土等灭火。

Use extinguishing media suitable for the materials that are burning, Such as dry powder, CO₂, soil sand and so on.

如果发生火灾,疏散该地区,并在安全距离下灭火。在安全距离灭火时,需要佩戴压力自主呼吸器。

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 6 of 14

As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance.

第六部分 泄漏应急处理

Section 6 - Accidental Release Measures

个人预防措施、防护设备和应急程序	在清理工作完成之前,禁止进入该区域。不要碰溢				
Personal Precautions, protective equipment, and	出的材料。按照第8节的规定,穿戴足够的个人				
emergency procedures	防护装备。				
	Restrict access to area until completion of				
	clean-up. Do not touch the spilled material. Wear				
	adequate personal protective equipment as				
02 02 02 02 02 02 0	indicated in Section 8.				
环保措施	防止材料污染土壤和进入下水道或水道。				
Environmental Precautions	Prevent material from contaminating soil and				
	from entering sewers or waterways.				
密封材料的方法	如果安全的话,就堵住泄漏。用干沙子或泥土把溢				
Methods and materials for Containment	出的液体堵住。立即清理溢出物。				
	Stop the leak if safe to do so. Contain the spilled				
	liquid with dry sand or earth. Clean up spills				
6, 6, 6, 6, 6, 6, 6, 8	immediately.				
清理材料的方法	用惰性吸附剂(干沙子或泥土)吸收溢出的材料。将				
Methods and materials for cleaning up	受污染的吸收剂倒入可接受的废物容器中。收集所				
	有受污染的吸收剂,并按照第13章的废弃弃置。				
	用清洁剂和水擦洗该区域;收集所有受污染的洗净				
	水,妥善处理。				
	Absorb spilled material with an inert absorbent				
	(dry sand or earth). Scoop contaminated				
	absorbent into an acceptable waste container.				
	Collect all contaminated absorbent and dispose				
	of according to directions in Section 13. Scrub				
	the area with detergent and water; collect all				
	contaminated wash water for proper disposal.				

第七部分 操作处置与储存

本报告是本公司遵循 www. ptc-testing.com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 7 of 14

Section 7 - Handling and Storage

操作	4	4	Ý.	Ý.	Ý.	Ý.	不要将锂电池模组和金属制品一同处理。不要:
Handling	S.C.						开, 拆解, 挤压或燃烧锂电池模组。确保工作场通风良好。防止粉尘的形成。
0 30							Don't handle Lithium Battery Module with
0 20							metalwork. Do not open, dissemble, crush or
(4)							burn Lithium Battery Module. Ensure good
0 6							ventilation/ exhaustion at the workplace.
c \ c							Prevent formation of dust.
							爆炸和着火防护信息:远离火源——严禁吸烟。
							Information about protection against explosion
							and fires: Keep ignition sources away- Do not
00	~0	~0	-20		~	-20	smoke.
储存							如果锂电池模组将进行超过3个月的长时间存储
Storage							建议定期对锂电池模组进行充电。
							If the Lithium Battery Module is subject to
							storage for such a long term as more than 3
							months, it is recommended to recharge the
							Lithium Battery Module periodically.
							建议长时间存储将存储温度控制在 0℃~35℃, to 85%RH.
							And recommended at 0°C~35°C, 45 to 85%R
							for long period storage.
							不要将锂电池模组随意的放置在箱子或抽屉,这 也许会使锂电池模组互相短路或被其他金属物。
							短路。
							Do not store Lithium Battery Module
							haphazardly in a box or drawer where they ma
							short-circuit each other or be short-circuited by
							other metal objects.
							放置于小孩不能接触的地方。
							Keep out of reach of children.
							不要将锂电池模组暴露在热源或火焰中。避免放
0 0							在阳光直射的地方。
~ 6~	Q'	Q V	6	6	6/	QN.	Do not expose Lithium Battery Module to heat

本报告是本公司遵循 www.ptc-testing.com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路 6 号 1 栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 8 of 14

1	Q.	8	Q"	é!	Q.	Q.	é (fire. Avoid storage in direct sunlight.
C								不要将锂电池模组与氧化物和酸性物质存储在一起。
ζC.								Do not store Lithium Battery Module together with oxidizing and acidic materials.

第八部分 接触控制和个人防护 Section 8 – Exposure Controls and Personal Protection

I	程控制	8.	8	8	8	Q.,	8,	使用当地的排气通风或其他工程控制来控制灰尘、
E	ngineei	ring C	ontrols					雾、烟雾和蒸汽的来源。
								Use local exhaust ventilation or other
								engineering controls to control sources of dust,
								mist, fumes and vapor.
								远离热源和明火。存放于阴凉干燥处。
								Keep away from heat and open flame. Store in a
	X	X	×	×	X	X	X	cool, dry place.
•	人防护							呼吸保护:正常情况下不需要。
Ρ	ersona	l Prote	ective E	quipm	ent			Respiratory Protection: Not necessary under
								normal conditions.
								皮肤和身体保护:在正常情况下不需要,如果处理
								打开或泄漏的锂电池模组,戴氯丁橡胶或丁腈橡胶
								手套。
								Skin and body Protection:Not necessary under
								normal conditions, Wear neoprene or nitrile
								rubber gloves if handling an open or leaking
								Lithium Battery Module.
								手保护:如果操作打开或泄漏的锂电池模组,应佩
								戴氯丁橡胶或天然橡胶手套。
								Hand protection: Wear neoprene or natural
								rubber material gloves if handling an open or
								leaking Lithium Battery Module.
								眼睛保护:在正常情况下不需要,如果处理打开或
								泄漏的锂电池模组,请佩戴安全眼镜。
								Eye Protection: Not necessary under normal
								conditions, Wear safety glasses if handling an

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋



Report No.: PTC24010313201S-LD01 **Effective Date: 2024.01.16** Page 9 of 14

	open or leaking Lithium Battery Module.
其他防护设备	在工作区域内准备一个安全的淋浴器和洗眼器。
Other Protective Equipment	Have a safety shower and eye wash fountain
	readily available in the immediate work area.
卫生措施	不要在工作区域吃、喝、抽烟。
Hygiene Measures	Do not eat, drink, or smoke in work area.
	保持工地整洁。
	Maintain good housekeeping.

第九部分 理化特性

Section 9 - Physical and Chemical Properties

1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	形态:固体						
	Form: Solid						
	形状: 长方体	4.4.4.4.4.4.4.4.4.					
物理状态	Shape: Cuboid						
Physical State	颜色: 黑色						
	Color: Black	olor: Black					
	气味: 无气味	0 0 0 0 0 0 0 0 0					
6, 6, 6,	Odor: Odorless						
pH值,表示浓度		不适用					
pH, with indication	of the concentration	Not applicable					
熔点与凝固点		没有相关资料					
Melting point/freezing point		No relevant information Available					
沸点		没有相关资料					
Boiling Point		No relevant information Available					
闪点		没有相关资料					
Flash Point		No relevant information Available					
上/下可燃性或爆炸	性极限	没有相关资料					
Upper/lower flammability or explosive limits		No relevant information Available					
蒸气压		不适用					
Vapor Pressure		Not applicable					
蒸汽密度(1个大气压)		不适用					
Vapor Density (Air = 1)		Not applicable					
密度/相对密度		没有相关资料					
Density/relative density		No relevant information Available					

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted. The report could not be copied without permission of the company.

精准通检测认证 (广东) 有限公司

Precise Testing & Certification (Guangdong) Co., Ltd. 广东省东莞市东城街道同新路 6 号 1 栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 10 of 14

水溶性	不相溶
Solubility in Water	Insoluble
自然温度	10000
Auto-ignition temperature	130°C
分解温度	没有相关资料
Decomposition temperature	No relevant information Available
蒸发率	没有相关资料
Evaporation rate	No relevant information Available
可燃性(土壤,大气)	没有相关资料
Flammability (soil, gas)	No relevant information Available
粘度	不适用
Viscosity	Not applicable

第十部分 稳定性和反应活性

Section 10 - Stability and Reactivity

稳定性	锂电池模组在正常工作条件下是稳定的。
Stability	The Lithium Battery Module is stable under
0 20 20 20 20 20 20	normal conditions.
避免条件 (静态放电,冲击,振动等)	锂电池模组不能有机械冲击。
Conditions to Avoid (e.g. static discharge, shock	Do not subject Lithium Battery Module to
or vibration)	mechanical shock.
	在运输期间的振动不能导致漏液,火灾或爆炸。
	Vibration encountered during transportation
	does not cause leakage, fire or explosion.
	不能拆开,碾碎,短路或错误的极性安装。
	Do not disassemble, crush, short or install with
	incorrect polarity.
	避免机械或电力滥用。
	Avoid mechanical or electrical abuse.
不相容材料	没有相关资料
Incompatible Materials	No relevant information Available
危险分解产品	这种材料如果燃烧或暴露在火中,可能会释放出有
Hazardous Decomposition Products	毒的烟雾
0 20 20 0 0 0 0 20 20	This material may release toxic fumes if burned
	or exposed to fire

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 11 of 14

危险反应的可能性	没有相关资料
Possibility of Hazardous Reaction	No relevant information Available

第十一部分 毒理学信息

Section 11 - Toxicological Information

刺激性	只有当内部电芯被机械、热或电滥用到损害外壳的
Irritation	程度时,才会发生刺激的风险。如果发生这种情况,皮肤、眼睛和呼吸道可能会受到刺激。
e to to to to to to to	Risk of irritation occurs only if the internal cell is mechanically, thermally or electrically abused to
e te te te te te te	the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory
0 00 00 00 00 00 00	tract may occur.
感光性	没有相关资料
Sensitization	No relevant information Available
神经系统影响 Neurological Effects	没有相关资料 No relevant information Available
生殖毒性	没有相关资料
Reproductive Toxicity	No relevant information Available
诱变(遗传反应)	没有相关资料
Mutagenicity (Genetic Effects)	No relevant information Available

第十二部分 生态学信息

Section 12 - Ecological Information

0	一般性注	释	20	.0	20	20	20	1级水危害(自评):对水有轻微危害。
C	Seneral	note:						Water hazard class 1(Self-assessment): slightly
20								hazardous for water.
3								不要让未经稀释的产品或大量的产品到达地下水,
30								水道或污水系统。
								Do not allow undiluted product or large quantities
10								of it to reach ground water, water course or
								sewage system.
	Q.C	Q.	S.C.	S. C.	Q.	S.C.	2 0	处置废弃电池时,远离火源,雨水和雪水。

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 12 of 14

	Dispose of batteries away from fire, rain and snow.
化学品在环境中的预期行为/可能的环境影响/生态毒性 Anticipated behavior of a chemical product in environment/possible environmental impace/ecotoxicity	没有相关资料 No relevant information Available
土壤中移动性	没有相关资料
Mobility in soil	No relevant information Available

持久性和降解性	没有相关资料		
Persistence and Degradability	No relevant information Available		
生物体内积累的潜伏	没有相关资料		
Bioaccumulation potential	No relevant information Available		
其他有害效应	没有相关资料		
Other Adverse Effects	No relevant information Available		

第十三部分 废弃处置

Section 13 - Disposal Considerations

废弃锂电池模组不能直接当作普通垃圾处理。

Disposal Lithium Battery Module cannot be directly treated as ordinary garbage.

产品处理建议:遵守当地、州和联邦法律法规。包装处理建议:注意废弃锂电池模组可能引起火灾,用胶带将锂电池模组端子绝缘。不要拆卸锂电池模组。完全排出容器(无泪滴,无粉末残留,仔细刮擦)。容器可以回收或再使用。遵守当地、州和联邦的法律法规。

Product disposal recommendation: Observe local, state and federal laws and regulations.

Packaging disposal recommendation: Be aware discarded Lithium Battery Module may cause fire, tape the Lithium Battery Module terminals to insulate them. Don't disassembly the Lithium Battery Module. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

第十四部分 运输信息

Section 14 - Transport Information

本锂电池模组 (M12-400)已通过 UN38.3 测试,并符合联合国关于危险货物运输的建议;国际航空运输协会危险品规定,以及美国交通部安全运输电动汽车的相关规定。

本报告是本公司遵循 www.ptc-testing.com服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 13 of 14

The Lithium Battery Module (M12-400) had passed the UN 38.3 test and also complies with the United Nations Recommendations on the Transport of Dangerous Goods; IATA Dangerous Goods regulations, and applicable U.S. DOT regulations for the safe transport of Lithium Battery Module.

国际航空运输协会《危险品规则》中, 锂电池模组被划分为 PI 965: 锂离子电芯/电池(UN 编号: UN3480); PI966: 与设备包装在一起的锂离子电芯/电池(UN 编号: UN3481); PI967: 安装在设备中的锂离子电芯/电池 (UN 编号: UN3481)。

In the IATA Dangerous Goods Regulations, Lithium Battery Module is divided into PI965: lithium ion cell/battery (UN Number: UN3480); PI 966: lithium ion cell/battery packed with equipment(UN Number: UN3481); PI 967: lithium ion cell/battery contained in equipment(UN Number: UN3481).

本锂电池模组根据国际航空运输协会 DGR 第 65 版新包装指令 965 Section IA; 966 Section I 和 967 Section I 进行运输。

The Lithium Battery Module is transported according to the NEW PACKING INSTRUCTION 965 Section IA; 966 Section I and 967 Section I of IATA DGR 65th edition.

锂电池模组根据《联合国危险品货物运输规章范本》,可作为"危险货物"处理,条件是包装牢固并防止产品短路。 Lithium Battery Module can be treated as "Dangerous goods" under the United Nations Recommendations on the Transport of Dangerous Goods, provided that packaging is strong and prevent the products from short-circuit.

UN编号: UN3480&UN3481

UN Number: UN3480&UN3481

运输方式:空运、海运、陆运、铁路运输。

The mode of transportation: Air transportation, Sea transportation, Road transportation, Railway transportation.

空运标签: 第九类危险品标签和仅限货机标签。

Label for Air transportation: Hazard Class 9 label and Cargo Aircraft only.

海运,陆运,铁路运输标签:第九类危险品标签。

Label for Sea transportation, Road transportation, Railway transportation: Hazard Class 9 label. 锂电池的国际运输有以下组织制订了规则:

International transport of lithium batteries is regulated by the following organizations:

- 国际民航组织 ICAO《危险物品航空安全运输技术导则》
- The International Civil Aviation Organization (ICAO) Technical Instructions.
- 国际航空运输协会 IATA《危险品规则》第 65 版
- The International Air transport Association (IATA) Dangerous Goods Regulations. 65th edition.
- 国际海事组织 IMO《国际海运危险货物规则》 IMDG(41-22)
- The International Maritime Dangerous Goods (IMDG) Code. IMDG(41-22)

第十五部分 法规信息

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋



Report No.: PTC24010313201S-LD01 **Effective Date:** 2024.01.16 Page 14 of 14

Section 15 - Regulatory Information

《危险品规则》

《Dangerous Goods Regulations》

《国际海运危险货物规则》

《International Maritime Dangerous Goods》

《联合国危险品货物运输规章范本》

《United Nations Recommendations on the Transport of Dangerous Goods Regulations》

《危险品货物分类和品名编号》

《Classification and code of Dangerous Goods》

《职业安全卫生法》

《Occupational Safety and Health Act》(OSHA)

《毒性物质控制法》

《Toxic Subatance Control Act》(TSCA)

《附加基金修正复审法 III (302/311/312/313)》

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》

参照联合国, 国家, 地方性法规。

In according with United Nations, country, and local laws.

第十六部分 其他信息

Section 16 - Other Information

以上信息被认为是准确的,代表了我们目前可以得到的信息。但是,我方不就该等信息作出能力保证或任何其他明示或暗示的保证,我们不承担因使用该等信息而产生的责任。使用者应自行进行调查,以确定有关资料是否适合其特定用途。虽然在准备本文所包含的数据时采取了合理的预防措施,但仅供您参考、考虑和调查。

The information above is believed to be accurate and represents the best information currently available to us. However, DGCTL makes no warranty of ability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation.

******	MSDS结束	******
******	end of MSDS	3 **************

本报告是本公司遵循 www. ptc-testing. com 服务通用条款所出具。 责任、保障和法律限制在服务通用条款已给了定义。

除非另有说明,此报告结果只对测试样品负责。本报告未经本公司许可,不可部分复制。

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission of the company.

精准通检测认证(广东)有限公司

Precise Testing & Certification (Guangdong) Co., Ltd.

广东省东莞市东城街道同新路6号1栋